



b3 Dispenser

SPECIFICATIONS

Configuration	Floorstanding,
Water Options	Chilled & Ambient Chilled, Hot & Ambient Chilled & Sparkling Chilled, Ambient & Sparkling Chilled, Hot & Sparkling
Dimensions WxDxH	Floorstanding: W12 x D14 x H42 inches W325 x D380 x H1065 mm
Dispenser Area Height	10.5 inches, 265mm
Water System	Direct Chill
Throughput	Chilled water 30 liters per hour Sparkling water 30 liters per hour Hot water 6 liters per hour
Water Temperature:	Chilled, Min 2C, Max 11C Hot Max 92C
Maximum running power consumption: (Watts)	Chilled & Ambient 100W Chilled, Hot, Ambient 600W Chilled, Ambient & Sparkling 140W Chilled, Hot & Sparkling 640W
Voltage	Hertz 50, Volts 110V / 220V
Contact-less add ons	Hands-free Dispenser Foot Switch Sterizen® Antimicrobial Touch panel Protectors, Touchless Dispense App
Accessories	7oz biodegradable paper cups 500ml Water bottles
Filtration Options	Carbon, Three Stage, Reverse Osmosis, Alkaline, Mineral
Drainage	Required only with Reverse Osmosis Filtration
Colour	Silver, Black
Refridgerant Gas	R134a 36mg